

## TABLE OF CONTENTS



<b>Biography</b> .....	5	<b>Brake Force and Corner Weight</b> .....	37
<b>Acknowledgments</b> .....	5	<b>Perfect Balance</b> .....	38
<b>Dedication</b> .....	6	<b>Static Weight Distribution</b> .....	39
<b>Foreword</b> .....	6	<b>The Second Law of Motion</b> .....	39
<b>Introduction</b> .....	7	<b>Dynamic Weight Distribution</b> .....	40
<b>Chapter 1: Energy Conversion</b> .....	9	<b>The Benefits of Perfect Balance</b> .....	41
The Conservation of Energy .....	9	<b>Front Brake Bias</b> .....	43
Where Energy Comes From .....	10	<b>Rear Brake Bias</b> .....	43
Friction .....	10	<b>Measuring Brake Balance</b> .....	44
Kinetic Energy .....	11	<b>Changing Brake Balance</b> .....	44
Potential Energy .....	13	<b>Chapter 5: Pedals, Boosters</b>	
Energy Transformation .....	14	<b>and Master Cylinders</b> .....	46
Energy and the Brake System .....	14	Brake Pedal Components .....	46
Calculating Brake System Temperature .....	15	OEM Brake Pedals .....	47
Importance of Brake Sizing .....	15	Racing Brake Pedals .....	48
<b>Chapter 2: Tires Stop the Car</b> .....	18	Brake Boosters .....	48
The First Law of Motion .....	18	Vacuum Boosters .....	48
Brake Forces .....	18	Hydraulic Boosters .....	50
Tire Slip .....	19	Master Cylinders .....	50
How Brake Forces are Generated .....	20	Master Cylinder Selection .....	52
The Mu-Slip Curve .....	22	Rear Brake Pressure Reduction .....	54
Choosing the Best Tires .....	24	Balance Bars .....	54
Calculating Maximum Deceleration .....	25	Proportioning Valves .....	55
<b>Chapter 3: Brake System Design</b> .....	27	<b>Chapter 6: Brake Fluid</b> .....	58
Driver Applied Force .....	27	Brake Fluid 101 .....	58
Brake System Overview .....	28	FMVSS116 .....	58
Brake Corner Gain .....	33	Dry Boiling Point .....	60
Summing Forces .....	34	Wet Boiling Point .....	61
Overall Brake System Gain .....	34	Water Adsorption .....	61
Calculating Deceleration .....	34	DOT Ratings .....	61
Calculating Stopping Distance .....	34	Brake Fluid Compatibility .....	64
Brake System Modifications .....	35	Brake Fluid Maintenance .....	64
<b>Chapter 4: Brake Balance</b> .....	37	Brake Bleeding .....	65
		<b>Chapter 7: Brake Lines and Hoses</b> .....	69

# TABLE OF CONTENTS



Hydraulic Circuit Design	69		
Brake Lines	70		
Flare Fittings	70		
Brake Hoses	71		
Banjo Fittings	72		
Stainless Steel Brake Hoses	73		
<b>Chapter 8: Brake Calipers</b>	<b>76</b>	<b>Chapter 11: Sports Car Brake Upgrade</b>	<b>118</b>
Hydraulic Gain	76	The Vehicle	119
Caliper Components	76	The Objective	119
Taper Wear	79	Picking the Right Parts	119
Piston Count	81	Bolting Them On	121
Caliper Mounting	82	The Results	124
One-Piece (Monoblock) Calipers	84		
Two-Piece Calipers	84	<b>Chapter 12: Racecar Brake Upgrade</b>	<b>126</b>
Knockback	84	The Vehicle	127
		The Objective	127
<b>Chapter 9: Brake Pads</b>	<b>88</b>	Front Brake Upgrade	127
Brake Pad Terminology	88	Rear Brake Upgrade	129
Coefficient of Friction	90	Apply System Upgrade	131
Coefficient of Friction Stability	91	Hoses, Fluids, and Pads	132
Brake Pad Fade	91	The Results	132
Friction Material Categories	92		
Friction Material Chemistries	93	<b>Chapter 13: Muscle Car Brake Upgrade</b>	<b>133</b>
Friction Mechanisms	96	The Vehicle	133
Brake System Break-In	97	The Objective	134
		Drum Brakes 101	134
<b>Chapter 10: Brake Rotors</b>	<b>100</b>	Picking The Right Parts	134
A Rotor Refresher	100	Bolting Them On	135
Rotor Terminology	101	Buttoning it Up	138
Effective Radius	103	The Results	138
Rotor Sizing	103		
Static Weight and Rotational Inertia	103	<b>Chapter 14: Hot Rod Brake Upgrade</b>	<b>139</b>
Rotor Cooling	104	The Vehicle	139
One-Piece (Fixed) Rotors	107	The Objective	139
Two-Piece (Floating) Rotors	107	Front Brake Upgrade	139
Solid Rotors	109	Brake Pedal Considerations	140
Vented Rotors	110	Master Cylinder Upgrade	142
Cross-Drilled Rotors	111	Brake Line and Proportioning	
Slotted Rotors	112	Valve Installation	142
Rotor Inspection	113	Brake Hoses	143
Thickness Variation	115	Brake Fluid Selection	143
		Parking Brake Installation	144
		The Results	144



# HOT ROD BRAKE UPGRADE

In many ways, hot rod builders are on their own when it comes to brake system component selection and system design. Unlike any of the production-based brake upgrades discussed this far, building a hot rod from scratch (or even from a kit) entails a unique collection of brake system considerations and constraints. With custom frames, powerful drivelines, modified bodies, and cut-and-paste suspension systems, there is little opportunity to learn from the original vehicle when the time comes to create your own hot rod brake system.

Yet the laws of physics still apply in these applications, making basic brake system design criteria just as important here as they were in Chapters 11, 12, and 13. The pages that follow will expose you to some of the most common design compromises, hardware considerations, and installation pitfalls that are either unique to, or exaggerated by, hot rod brake systems.

## The Vehicle

The subject of this hot rod brake upgrade project began life as a 1940 Ford pickup truck. Although it still possesses some token bits of the original body and frame, little else resembles what rolled off of the assembly line over 60 years ago. Custom roadster coachwork, independent front suspension, Chevy power under the hood, and a host of complex chassis changes only begin to describe the level of change this truck has experienced.

Although originally equipped with hydraulic brakes (mechanical brakes were only dropped the year before in 1939), the single-circuit master cylinder and four-wheel drum brake layout was dated at



*We were fortunate to catch this 1940 Ford hot rod pickup in the middle of its own brake upgrade project. When embarking on your own hot rod brake system upgrade, it sure helps to have the vehicle up off the ground in a clean and well-lit garage. If possible, having most of the body and powertrain out of the way makes the job that much easier. (Randall Shafer)*

best. Therefore, as long as the rest of the truck was being significantly modified and updated, the brake system was upgraded as well.

## The Objective

Like most vehicles of this type, this hot rod was primarily designed for cruising along on a Sunday afternoon drive. Therefore, increased thermal capacity was not high on the list of needs or wants. At the same time, optimizing brake pedal feel was not critical for the truck's intended use. In short, the most important

brake system performance requirement was to slow the truck in a stable fashion during emergency-type events. Naturally, the parts had to look good (since that's a big part of what hot rodding is all about), but performing a single stop quickly and reliably from a moderate speed was the most stringent brake system performance design target.

## Front Brake Upgrade

The forward frame rails of the truck had already been modified to accept one of the most common independent front



*It took a significant amount of modification to adapt a Mustang II front suspension to the stock front frame rails. However, the front brake hardware remains essentially unchanged from the Mustang II design. Note that many hot rodders upgrade their Mustang II front end with a set of 11.0-inch diameter rotors and aftermarket caliper mounting brackets. (Randall Shafer)*



*The Mustang II front brake calipers contain relatively large brake pads held in place by floating caliper bodies. The single piston in each caliper was designed to be offset relative to the center of the rotor friction disc, resulting in a larger effective radius. In plain English, this means higher gain is possible in a smaller package. (Randall Shafer)*

suspensions used in the hot rodding community. Lifted straight from a Ford Mustang II, this setup can be found hanging off the front end of countless hot rods today. In this application, the upper and lower control arms had already been replaced with custom tubular pieces, but the front uprights, bearings, and brake hardware were straight from the Ford parts bin.

Chosen more for availability and fitment than for thermal mass and effective radius, the front rotors measured a relatively small 9.0 inches in diameter and 0.9 inches in thickness. Although the straight vanes in the vented friction discs were not expected to be as efficient as curved vanes would have been, any front rotors would be more thermally robust than the stock front drums.

Like the front rotors, the front calipers were chosen more for convenience than for performance. These remanufactured single-piston calipers were based on the

original Mustang II floating design. Their compact dimensions were the final consideration, as this would lead to flexibility in wheel selection later in the project.

Although a more modern Ford rear axle had been installed, in the interest of both time and money it was decided to leave the rear drum brakes in place. Of course they would receive a fresh coat of paint and fresh internal components, but with so little weight over the rear tires there was no reason to improve their performance. Even though it was still a pickup truck, its heavy hauling days were over.

### Brake Pedal Considerations

In 1940, vacuum boosters were still several decades away from becoming mainstream brake system components. Therefore, because the truck was originally built without a vacuum booster (in other words, built with manual brakes), the brake pedal ratio was exceptionally high compared to conventional standards. Employing a pedal ratio of approximately 8.0:1, the stock brake pedal was required to swing through a relatively long arc as brake pressure was generated in the master cylinder.

Since the truck's master cylinder was originally mounted beneath the floor of the vehicle, retrofitting a vacuum booster,



*While the stock single-circuit master cylinder was swapped for a tandem unit, its location under the vehicle was retained. The tight confines dictated that an opening be cut in the floorpan to allow access to the brake fluid reservoir. Check out the elegant routing of the custom-bent brake lines! (Randall Shafer)*